

| | | | |
|---|---|-------------|--------------|
| Outdoor unit | RXP20N5V1B | | |
| Indoor unit | FTXP20N5V1B | | |
| Function | | | |
| Kühlung | Ja | | |
| Heizen | Ja | | |
| | Average (mandatory) Warmer (if designated) Colder (if designated) | | |
| | Ja Ja Nein | | |
| Element | Symbol | Wert | Gerät |
| Design Load | | | |
| Kühlung | Pdesignc | 2.00 | kW |
| heating / Average | Pdesignh | 2.20 | kW |
| heating / Warmer | Pdesignh | 1.18 | kW |
| heating / Colder | Pdesignh | 1.30 | kW |
| Deklarierte Leistung* für Kühlen, bei Innentemperatur 27 (19) °C und Außentemperatur Tj | | | |
| Tj = 35°C | Pdc | 2.00 | kW |
| Tj = 30°C | Pdc | 1.47 | kW |
| Tj = 25°C | Pdc | 1.23 | kW |
| Tj = 20°C | Pdc | 1.30 | kW |
| Declared capacity* for heating / Average season , at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = -7°C | Pdh | 1.95 | kW |
| Tj = 2°C | Pdh | 1.18 | kW |
| Tj = 7°C | Pdh | 0.910 | kW |
| Tj = 12°C | Pdh | 1.06 | kW |
| Tj = Bivalent temperature | Pdh | 1.95 | kW |
| Tj = operating limit | Pdh | 2.05 | kW |
| Declared capacity* for heating / Warmer season , at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = 2°C | Pdh | 1.18 | kW |
| Tj = 7°C | Pdh | 0.910 | kW |
| Tj = 12°C | Pdh | 1.06 | kW |
| Tj = Bivalent temperature | Pdh | 1.18 | kW |
| Tj = operating limit | Pdh | 2.05 | kW |
| Declared capacity* for heating / Colder season , at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = -7°C | Pdh | | kW |
| Tj = 2°C | Pdh | | kW |
| Tj = 7°C | Pdh | | kW |
| Tj = 12°C | Pdh | | kW |
| Tj = Bivalent temperature | Pdh | | kW |
| Tj = operating limit | Pdh | | kW |
| Tj = -15°C | Pdh | | kW |
| Bivalent temperature | | | |
| heating / Average | Tbiv | -7.0 | °C |
| heating / Warmer | Tbiv | 2 | °C |
| heating / Colder | Tbiv | 0 | °C |
| Cycling interval capacity | | | |
| for cooling | Pcyc | | kW |
| for heating | Pcych | | kW |
| Degradation co-efficient cooling** | Cdc | 0.25 | - |
| Electric power input in power models other than 'active mode' | | | |
| Off mode | Poff | 0.001 | kW |
| Standby mode | Psb | 0.001 | kW |
| Thermostat-off mode | PTO | 0 | kW |
| Crankcase heater mode | PCK | 0 | kW |
| Capacity control | | | |
| Fest | N | | |
| Gestaffelt | N | | |
| Variable | N | | |
| Contact details for obtaining more information | Daikin Europe N.V. Zandvoordestraat 300, B-8400 Oostende, Belgium | | |

* for staged capacity units, two values divided by a slash (/) will be declared in each box in the section 'Declared capacity of the unit' and 'Declared EER/COP' of the unit.

** if default Cd = 0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating of cooling cycling test value is required.