

Indoor unit model name FDT40VH Outdoor unit model name SRC40ZSX-W1

Refrigerant	R32	GWP	6	75	
contribute less to appliance contair would be leaked over a period of	global warming than as a refrigerant fluid v to the atmosphere, th	n a refrigerant with a GWP e he impact on to interfere wi	t with hi equal to global v	gher GWP, if lea 675. This means warming would be	lobal warming potential (GWP) would ked to the atmosphere. This that if 1kg of this refrigerant fluid 675 times higher than 1kg of CO2, yourself or disassemble the product
Cooling mode					
SEER		8.7			
Energy efficie		A+++	1.3.67		
Design load (I		4.0		nor voor hooo	d on standard tost results
Energy consu Actual energ					d on standard test results. used and where it is located.
Heating mode (A	verage)				
SCÕP `	U ,	4.7			
Energy efficie	ncy class	A++			
Design load (I			kW	`	
Declared capa			kW	(-10°C)	
Back up heati			kW	(-10°C)	
Energy consu					d on standard test results.
Actual energ	gy consumption will	ll depend on	now th	ne appliance is	used and where it is located.
Heating mode (V	/armer) Optional				
SCOP		-			
Energy efficie		-			
Design load (I			kW	(2°C)	
Declared capa			kW	(2°C)	
Back up heati			kW	(2°C)	
Energy consu					d on standard test results.
Actual energ	gy consumption wil	ll depend on	how th	ne appliance is	used and where it is located.
Heating mode (C	older) Optional				
SCOP		-			
Energy efficie		-	1.1.1.1	(00°)	
Design load (I			kW	(-22°C)	
Declared capa			kW kW	(-22°C)	
Back up heati				(-22°C)	d on standard tost results
Energy consu					d on standard test results. used and where it is located.
Sound nower	level (indoor)	50		dB(A)	
		50			
	level (outdoor)	50 63		dB(A)	