

Indoor unit model name SRK71ZR-W Outdoor unit model name FDC71VNX-W

Pofrigorant	Daa	GWP	6	75	
Refrigerant	R32	GVVP	0	5	
contribute less to appliance contain would be leaked over a period of	global warming than a ns a refrigerant fluid wi to the atmosphere, the	a refrigerant th a GWP e impact on interfere wi	with hi qual to global v	ant with lower global warming poten her GWP, if leaked to the atmosphe 675. This means that if 1kg of this ref arming would be 675 times higher th frigerant circuit yourself or disassem	e. This rigerant fluid an 1kg of CO2,
Cooling mode					
SEER		6.8			
Energy efficie		A++			
Design load (7.1		an year based on standard to	
Energy consu				er year.based on standard tes e appliance is used and where it	
Actual energy	gy consumption win t		1000 1	e appliance is used and where it	s located.
Heating mode (A	verage)				
SCOP		4.6			
Energy efficie		A+			
Design load (kW	(-10°C)	
Declared cap		5.80		(-10°C)	
Back up heati			kW	(-10°C)	1
Energy consu				er year.based on standard tes	
Actual energy	gy consumption will a	aepena on	now tr	e appliance is used and where it	s located.
Heating mode (V	Varmer) Optional				
SCOP	<i>,</i> .	-			
Energy efficie	ncy class	-			
Design load (Pdesignh)	-	kW	(2°C)	
Declared cap	acity	-	kW	(2°C)	
Back up heat	ing capacity		kW	(2°C)	
Energy consu				er year.based on standard tes	
Actual energy	gy consumption will o	depend on	how th	e appliance is used and where it	is located.
Heating mode (C	Coldor) Optional				
SCOP		_			
Energy efficie	ncy class	-			
Design load (-	kW	(-22°C)	
Declared cap	U ,		kW	(-22°C)	
Back up heati			kW	(-22°C)	
Energy consu	0 1 2			er year.based on standard tes	st results
				e appliance is used and where it	
				••	
Sound power	level (indoor)	57		dB(A)	
	level (indoor) level (outdoor)	57 66		dB(A) dB(A)	