

Indoor unit model name SRK20ZS-WF, SRK25ZS-WF x 2 units Outdoor unit model name SCM50ZS-W

Refrigerant	R32	GWP		675	
		0			
-	-	-	-	-	bal warming potential (GWP) would
					d to the atmosphere. This
	-		-		nat if 1kg of this refrigerant fluid
	-		-	-	675 times higher than 1kg of CO2,
	• •		ith the	refrigerant circuit yo	ourself or disassemble the product
yourself and alw	ays ask a professional	•			
Cooling mode					
SEER		7.4			
Energy efficie	encv class	A++			
Design load (kW		
Energy consu				per year.based	on standard test results.
					sed and where it is located.
Heating mode (A	(verage)				
SCOP	weraye)	4.4			
Energy efficie	ency class	4.4 A+			
Design load (kW	(-10°C)	
Declared cap		4.70		(-10°C)	
Back up heat			kW	(-10°C)	
Energy consu					on standard test results.
					sed and where it is located.
	Varmer) Optional				
SCOP		5.9			
Energy efficie		A+++		(0°0)	
Design load (8 /		kW	(2°C) (2°C)	
Declared cap Back up heat		6.40	kW	(2°C)	
Energy consu				· ·	on standard test results
					on standard test results.
					sed and where it is located.
Actual ener	gy consumption will				
Actual ener Heating mode (C SCOP	gy consumption will Colder) Optional				
Actual ener Heating mode (C SCOP Energy efficie	gy consumption will Colder) Optional ency class	depend on - -	how	the appliance is us	
Actual ener Heating mode (C SCOP Energy efficie Design load (gy consumption will Colder) Optional ency class Pdesignh)	depend on - -	how	the appliance is us (-22°C)	
Actual ener Heating mode (C SCOP Energy efficie Design load (Declared cap	gy consumption will Colder) Optional ency class Pdesignh) acity	depend on - - - -	how kW kW	(-22°C) (-22°C)	
Actual energy Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heat	gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity	depend on - - - - -	kW kW kW	(-22°C) (-22°C) (-22°C) (-22°C)	sed and where it is located.
Actual energy Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heat Energy consu	gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity imption,	depend on - - - - - - -	kW kW kW kW	(-22°C) (-22°C) (-22°C) (-22°C) per year.based	sed and where it is located. on standard test results.
Actual energy Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heat Energy consu	gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity imption,	depend on - - - - - - -	kW kW kW kW	(-22°C) (-22°C) (-22°C) (-22°C) per year.based	sed and where it is located.
Actual energy Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heat Energy consu Actual energy	gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity imption, gy consumption will	depend on - - - - - depend on	kW kW kW kW	(-22°C) (-22°C) (-22°C) (-22°C) per year.based the appliance is us	on standard test results.
Actual energy Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heat Energy consu Actual energy	gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity imption,	depend on - - - - - - -	kW kW kW kW	(-22°C) (-22°C) (-22°C) (-22°C) per year.based the appliance is us dB(A) * The sou	sed and where it is located. on standard test results.