

Indoor unit model name SRK20ZS-WF, SRK25ZS-WF, SRK50ZS-WF Outdoor unit model name SCM71ZS-W

Refrigerant	R32	GWP		675
contribute less to appliance contain would be leaked over a period of	o global warming than ns a refrigerant fluid w to the atmosphere, th	a refrigeran vith a GWP e e impact on o interfere w	t with h equal to global	perant with lower global warming potential (GWP) would higher GWP, if leaked to the atmosphere. This o 675. This means that if 1kg of this refrigerant fluid warming would be 675 times higher than 1kg of CO2, refrigerant circuit yourself or disassemble the product
Cooling mode				
SEER		6.8		
Energy efficie		A++	1.3.47	
Design load (kW	nor year based on standard test results
Energy consu Actual energe				per year.based on standard test results. the appliance is used and where it is located.
Heating mode (A				
SCOP	(iolugo)	4.2		
Energy efficie	encv class	A+		
Design load (kW	(-10°C)
Declared cap			kW	(-10°C)
Back up heat	ing capacity	0	kW	(-10°C)
Energy consu				per year based on standard test results.
Actual energy	gy consumption will	depend on	how	the appliance is used and where it is located.
Heating mode (V	Varmer) Optional			
		5.4		
I SCOP		-		
SCOP Energy efficie	ency class	A+++		
Energy efficie	-		kW	(2°C)
	Pdesignh)	8.5	kW kW	(2°C) (2°C)
Energy efficie Design load (Pdesignh) acity	8.5 8.5		
Energy efficie Design load (Declared cap	Pdesignh) acity ing capacity	8.5 8.5 0	kW kW	(2°C)
Energy efficie Design load (Declared cap Back up heati Energy consu	Pdesignh) acity ing capacity imption,	8.5 8.5 0 2205	kW kW kWh	(2°C) (2°C)
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energy	Pdesignh) acity ing capacity imption, gy consumption will	8.5 8.5 0 2205	kW kW kWh	(2°C) (2°C) per year.based on standard test results.
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energ Heating mode (C SCOP	Pdesignh) acity ing capacity imption, gy consumption will Colder) Optional	8.5 8.5 0 2205	kW kW kWh	(2°C) (2°C) per year.based on standard test results.
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energ Heating mode (C SCOP Energy efficie	Pdesignh) acity ing capacity imption, gy consumption will Colder) Optional ency class	8.5 8.5 0 2205 depend on -	kW kW kWh how	(2°C) (2°C) per year.based on standard test results. the appliance is used and where it is located.
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energy Heating mode (C SCOP Energy efficie Design load (Pdesignh) acity ing capacity imption, gy consumption will Colder) Optional ency class Pdesignh)	8.5 8.5 0 2205 depend on -	kW kW kWh how	(2°C) (2°C) per year.based on standard test results. the appliance is used and where it is located. (-22°C)
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energy Heating mode (C SCOP Energy efficie Design load (Declared cap	Pdesignh) acity ing capacity imption, gy consumption will Colder) Optional ency class Pdesignh) acity	8.5 8.5 0 2205 depend on - - -	kW kWh how kW kW	(2°C) (2°C) per year.based on standard test results. the appliance is used and where it is located. (-22°C) (-22°C)
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energy Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heati	Pdesignh) acity ing capacity imption, gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity	8.5 8.5 0 2205 depend on - - - -	kW kWh how kW kW kW	(2°C) (2°C) per year.based on standard test results. the appliance is used and where it is located. (-22°C) (-22°C) (-22°C) (-22°C)
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energy Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heati Energy consu	Pdesignh) acity ing capacity imption, gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity imption,	8.5 8.5 0 2205 depend on - - - - - - -	kW kWh how kW kW kW kW	(2°C) (2°C) per year.based on standard test results. the appliance is used and where it is located. (-22°C) (-22°C) (-22°C) per year.based on standard test results.
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energ Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heati Energy consu	Pdesignh) acity ing capacity imption, gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity imption,	8.5 8.5 0 2205 depend on - - - - - - -	kW kWh how kW kW kW kW	(2°C) (2°C) per year.based on standard test results. the appliance is used and where it is located. (-22°C) (-22°C) (-22°C) (-22°C)
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energ Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heati Energy consu Actual energ	Pdesignh) acity ing capacity imption, gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity imption, gy consumption will	8.5 8.5 0 2205 depend on - - - - - - - - - - - - - - - - - - -	kW kWh how kW kW kW kW	(2°C) (2°C) per year.based on standard test results. the appliance is used and where it is located. (-22°C) (-22°C) (-22°C) (-22°C) per year.based on standard test results. the appliance is used and where it is located.
Energy efficie Design load (Declared cap Back up heati Energy consu Actual energy Heating mode (C SCOP Energy efficie Design load (Declared cap Back up heati Energy consu Actual energy	Pdesignh) acity ing capacity imption, gy consumption will Colder) Optional ency class Pdesignh) acity ing capacity imption,	8.5 8.5 0 2205 depend on - - - - - - -	kW kWh how kW kW kW kW	(2°C) (2°C) per year.based on standard test results. the appliance is used and where it is located. (-22°C) (-22°C) (-22°C) per year.based on standard test results.