

<b>Capacity</b>	Cooling / Heating	7,1 (1,8–7,8) / 7,3 (1,5–9,4)	kW
<b>Power Supply</b>	Into Outdoor Unit	220 - 240 / 1 / 50	V / Ph / Hz
<b>Power Input</b>	Cooling / Heating	2,03 / 1,87	kW
<b>Rated Power Input</b>	Cooling / Heating	3,5	kW
<b>Power Current</b>	Cooling / Heating	9,0 / 9,3	A
<b>Rated Power Current</b>	Cooling / Heating	14	A
<b>Pdesign</b>	Cooling / Heating	7,1 / 5,6	kW
<b>SEER / SCOP</b>	-	7,0 / 4,3	W / W
<b>Air Flow</b>	Indoor Unit	1000 / 850 / 760 / 580 / 520 / 450 / 400	m <sup>3</sup> / h
<b>Air Flow</b>	Outdoor Unit	3600	m <sup>3</sup> / h
<b>Sound Pressure Level at 1 m</b>	Indoor Unit	48 / 44 / 41 / 40 / 38 / 36 / 33 / 27	dB(A)
<b>Sound Pressure Level at 1 m</b>	Outdoor Unit	59	dB(A)
<b>Sound Power Level</b>	Indoor unit	65 / 59 / 56 / 55 / 53 / 51 / 48	dB(A)
<b>Sound Power Level</b>	Outdoor unit	70	dB(A)
<b>Dehumidifying Volume</b>	-	2,4	l / h
<b>Refrigerant / Charge / Eq. CO2</b>	-	R32 / 1,40 / 0,94	type / kg / t
<b>Additional Refrigerant</b>	-	40	g / m
<b>Refrigerant Liquid Pipe</b>	Diameter	01.04.2006	inch / mm
<b>Refrigerant Gas Pipe</b>	Diameter	05.08.2016	inch / mm
<b>Max pipe length without additional refrigerant</b>	-	5	m
<b>Min. / Max. Pipe Length</b>	-	Mrz 25	m
<b>Max. Elevation</b>	-	10	m
<b>Dimension (w x h x d)</b>	Indoor Unit	993 × 311 × 222	mm
<b>Dimension (w x h x d)</b>	Outdoor Unit	958 × 660 × 402	mm
<b>Package (w x h x d)</b>	Indoor Unit	1055 × 385 × 298	mm
<b>Package (w x h x d)</b>	Outdoor Unit	1032 × 456 × 737	mm
<b>Net / Gross Weight</b>	Indoor Unit	13,0 / 15,5	kg
<b>Net / Gross Weight</b>	Outdoor Unit	45,0 / 49,5	kg
<b>Set Temperature range</b>	-	16 ~ 30	°C
<b>Operating Temperature Range</b>	Cooling	-15 ~ 50	°C
<b>Operating Temperature Range</b>	Heating	- 25 ~ 30	°C