Product Information



PRODUCT FICHE

Energy labelling Regulation: (EU) 811/2013 Ecodesign Regulation: (EU) 813/2013

Heat pump combination	n neater	Tank	EKHWS150D3V3 EKHWS150D3V3
ndoor unit sound power (*)		[dB(A)]	
outdoor unit sound power (*) Vater heating	Declared load profile	[dB(A)]	62.0
	Energy efficiency class	-	A
pace Heating verage climate (Design temperature = -10°C)	Energy efficiency class 55°C (High temp. app.)	-	A++
Water heating	Water heating energy efficiency (ղ _W ի)	[%]	87
	Annual energy consumption	[kWh]	1,184
Space Heating	Prated (declared heating capacity) @ -10°C	[kW]	11.0
		[%]	134
	Seasonal space heating efficiency (η (η _S)		104
ff peak operation function integrated in Heat pump	Annual energy consumption	[kWh] Y/N	false
older climate (Design temperature = -22°C)			
Water heating	Water heating energy efficiency (n _{Wh})	[%]	69
Space Heating	Annual electricity consumption (AEC)	[kWh]	1,491
	Prated (declared heating capacity) @ -22°C	[kW]	11.0
	Seasonal space heating efficiency (η (η _S)	[%]	120
	Annual energy consumption	[kWh]	
armer climate (Design temperature = 2°C)			100
Water heating Space Heating	Water heating energy efficiency (n _W h)	[%]	100
	Annual electricity consumption (AEC)	[kWh]	1,023
	Prated (declared heating capacity) @ 2°C	[kW]	12.1
	Seasonal space heating efficiency (η _S)	[%]	172
	Annual energy consumption	[kWh]	
codesign technical data		Y/N	Yes
Product description	Air-to-water heat pump Water-to-water heat pump	Y/N	No
	Brine-to-water heat pump	Y/N	No
	Low-temperature heat pump Equipped with a supplementary heater	Y/N Y/N	No Yes
in to weeken welf	Heat pump combination heater	Y/N 3	Yes
ir to water unit rine/water to water unit	Rated airflow (outdoor)	[m ³ /h]	4,220
	Rated water/brine flow (outdoor H/E)	[m ³ /h]	
Other	Capacity control	<u>-</u> [kW]	Inverter 0.023
	Poff (Power consumption Off mode)	DAAD	0.000
	Pto (Power consumption Thermostat off mode)	[kW]	0.023
	P _{SD} (Power consumption Standby mode)	[kW]	0.023
	PCK (Power crankcase heater model)	[kW]	0.000
	• • •	[kWh]	5.610
	Qelec (Daily electricity consumption)		0.010
	Qfuel (Daily fuel consumption)	[kWh]	
rt load conditions space heating average climate			
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	9.4
	COP _d (declared COP)	-	2.02
	Cdh (degradation coefficient)		1.0
B) condition (2°C) (C) condition (7°C)	Pdh (declared heating capacity)	[kW]	6.2
	-	-	3.28
	COP _d (declared COP)		
	Cdh (degradation coefficient)		1.0 4.4
	Pdh (declared heating capacity)	[]	
	COP _d (declared COP)		4.88
	Cdh (degradation coefficient)	-	1.0
(D) (D) condition (12°C)	Pdh (declared heating capacity)	[kW]	5.3
	COP _d (declared COP)		6.58
	Cdh (degradation coefficient)		1.0
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-10
	Pdh (declared heating capacity)	[kW]	7.8
	COPd (declared COP)	-	1.70
	WTOL (Heating water Operation Limit)	[°C]	55
(F) Tbivalent temperature	^T blv	[°C]	-6
) Ibivalent temperature	Pdh (declared heating capacity)	[kW]	9.4
, invalent temperature			
7 ibivalent temperature	an (accounted heating capacity)		0.00
/ Idvalent temperature	COPd (declared COP)	-	2.09
apacity of the back-up heater integrated in the unit		- [kW]	2.09

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.dalkin.eu'

(') Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3

This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.