VDAIKIN

Energy labelling Regulation: (EU) 811/2013 Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump combination heater		Indoor Tank	EBLA16DA3W1 / EKHWS150D3V3 EKHWS150D3V3
ndoor unit sound power (*)		[dB(A)]	
Dutdoor unit sound power (*) Vater heating	Declared load profile	[dB(A)]	62.0 L
-	Energy efficiency class Energy efficiency class 55°C (High temp. app.)	-	A A++
pace Heating verage climate (Design temperature = -10°C)	Energy efficiency class 55°C (High temp. app.)	-	
Nater heating	Water heating energy efficiency $(n_{W}h)$	[%]	87
	Annual energy consumption	[kWh]	1,184
Space Heating	Prated (declared heating capacity) @ -10°C	[kW]	12.0
	Seasonal space heating efficiency (η (η _S)	[%]	132
	Annual energy consumption	[kWh]	
ff peak operation function integrated in Heat pump older climate (Design temperature = -22°C)		<u>Y/N</u>	false
Nater heating	Water heating energy efficiency (η _W)	[%]	69
	Annual electricity consumption (AEC)	[kWh]	1,491
Space Heating	Prated (declared heating capacity) @ -22°C	[kW]	12.0
	Seasonal space heating efficiency (η (η _S)	[%]	121
	Annual energy consumption	[kWh]	
/armer climate (Design temperature = 2°C) /ater heating		[%]	100
	Water heating energy efficiency (n _W h)		_
Space Heating	Annual electricity consumption (AEC)	[kWh] [kW]	1,023 12.1
	Prated (declared heating capacity) @ 2°C		172
	Seasonal space heating efficiency (η _S)	[%]	1/2
codesign technical data	Annual energy consumption	[kWh]	
Product description	Air-to-water heat pump	Y/N	Yes
	Water-to-water heat pump Brine-to-water heat pump	<u>Y/N</u> <u>Y/N</u>	No No
	Low-temperature heat pump	Y/N Y/N	No Yes
	Equipped with a supplementary heater Heat pump combination heater	Y/N	Yes
ir to water unit	Rated airflow (outdoor)	[m ³ /h]	5,100
rine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]	
Dther	Capacity control	- [kW]	Inverter 0.023
	P _{Off} (Power consumption Off mode)		
	Pto (Power consumption Thermostat off mode)	[kW]	0.023
	P _{SD} (Power consumption Standby mode)	[kW]	0.023
	PCK (Power crankcase heater model)	[kW]	0.000
		[kWh]	5.610
	Q _E _{EC} (Daily electricity consumption)		
	Q _{fUC} (Daily fuel consumption)	[kWh]	
art load conditions space heating average climate a) condition (-7°C)		[kW]	9.4
B) condition (2°C)	Pdh (declared heating capacity)	[]	
	COP _d (declared COP)	-	1.95
	Cdh (degradation coefficient)	-	1.0 6.9
	Pdh (declared heating capacity)	[kW]	
	COP _d (declared COP)	-	3.27
	Cdh (degradation coefficient)	-	1.0
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.4
	COP _d (declared COP)	-	4.93
	Cdh (degradation coefficient)		1.0
(D) (D) condition (12°C)	Pdh (declared heating capacity)	[kW]	5.3
	COP _{CI} (declared COP)	-	6.60
	Cdh (degradation coefficient)		1.0
E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C] [kW]	-10 8.0
	Pdh (declared heating capacity)	[[(]]]	
	COP _C (declared COP)	-	1.67
	WTOL (Heating water Operation Limit)	[°C]	55
(F) Tbivalent temperature	Tblv	[°C]	-5
	Pdh (declared heating capacity)	[kW]	10.1
	COP _d (declared COP)	-	2.13
apacity of the back-up heater integrated in the unit		[kW]	
	PSUP back-up heater (@Tdesignh: -10°C)		
upplementary capacity at P_design	P _{SUD} (@Tdesignh: -10°C)	[kW]	4.1

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals. Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu' (') Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3 This data is for comparison of Energy efficiencies according to the gualation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.