

Product Information



Energy labelling Regulation: (EU) 811/2013

Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump combination heater		Outdoor	EPRA14DAW17
		Indoor	ETVX16S18EA9W7
Indoor unit sound power (*)		[dB(A)]	44.0
Outdoor unit sound power (*)		[dB(A)]	54.0
Water heating	Declared load profile	-	L
	Energy efficiency class	-	A
Space Heating	Energy efficiency class 55°C (High temp. app.)	-	A++
Average climate (Design temperature = -10°C)			
Water heating	Water heating energy efficiency (η_{Wh})	[%]	106
	Annual energy consumption	[kWh]	969
Space Heating	P_{rated} (declared heating capacity) @ -10°C	[kW]	13
	Seasonal space heating efficiency (η_{SS})	[%]	142
	Annual energy consumption	[kWh]	7,122
off peak operation function integrated in Heat pump		Y/N	false
Colder climate (Design temperature = -22°C)			
Water heating	Water heating energy efficiency (η_{Wh})	[%]	91
	Annual electricity consumption (AEC)	[kWh]	1,124
Space Heating	P_{rated} (declared heating capacity) @ -22°C	[kW]	13
	Seasonal space heating efficiency (η_{SS})	[%]	126
	Annual energy consumption	[kWh]	9,589
Warmer climate (Design temperature = 2°C)			
Water heating	Water heating energy efficiency (η_{Wh})	[%]	117
	Annual electricity consumption (AEC)	[kWh]	876
Space Heating	P_{rated} (declared heating capacity) @ 2°C	[kW]	14.1
	Seasonal space heating efficiency (η_{SS})	[%]	172
	Annual energy consumption	[kWh]	4,316
Ecodesign technical data			
Product description			
	Air-to-water heat pump	Y/N	Yes
	Water-to-water heat pump	Y/N	No
	Brine-to-water heat pump	Y/N	No
	Low-temperature heat pump	Y/N	No
	Equipped with a supplementary heater	Y/N	Yes
	Heat pump combination heater	Y/N	Yes
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	3
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]	3
Other			
	Capacity control	-	Inverter
	P_{Off} (Power consumption Off mode)	[kW]	0.031
	P_{TO} (Power consumption Thermostat off mode)	[kW]	0.033
	P_{SB} (Power consumption Standby mode)	[kW]	0.042
	P_{CK} (Power crankcase heater model)	[kW]	0.000
	Q_{elec} (Daily electricity consumption)	[kWh]	4.650
	Q_{fuel} (Daily fuel consumption)	[kWh]	
Part load conditions space heating average climate			
(A) condition (-7°C)			
	P_{dh} (declared heating capacity)	[kW]	11.1
	COP_d (declared COP)	-	2.43
	C_{dh} (degradation coefficient)	-	1.0
(B) condition (2°C)			
	P_{dh} (declared heating capacity)	[kW]	6.7
	COP_d (declared COP)	-	3.52
	C_{dh} (degradation coefficient)	-	1.0
(C) condition (7°C)			
	P_{dh} (declared heating capacity)	[kW]	6.5
	COP_d (declared COP)	-	4.54
	C_{dh} (degradation coefficient)	-	1.0
(D) (D) condition (12°C)			
	P_{dh} (declared heating capacity)	[kW]	5.2
	COP_d (declared COP)	-	5.97
	C_{dh} (degradation coefficient)	-	1.0
(E) Tol (temperature operating limit)			
	T_{ol} (temperature operating limit)	[°C]	-10
	P_{dh} (declared heating capacity)	[kW]	12.5
	COP_d (declared COP)	-	2.12
	WTOL (Heating water Operation Limit)	[°C]	55
(F) Tbialent temperature			
	T_{blv}	[°C]	-10
	P_{dh} (declared heating capacity)	[kW]	12.5
	COP_d (declared COP)	-	2.12
Capacity of the back-up heater integrated in the unit			
	P_{sup} back-up heater (@ $T_{designh}$: -10°C)	[kW]	9.0
Supplementary capacity at P_{design}			
	P_{sup} (@ $T_{designh}$: -10°C)	[kW]	13

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu'

(*) Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3
This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.
Depending on your application and the product selected an additional supplementary heater may have to be installed.
