

Indoor unit model name SRK50ZSX-W Outdoor unit model name SRC50ZSX-W2

Refrigerant	R32	GWP		675
Reingerant	NJZ	000	,	515
contribute less t appliance conta would be leaked over a period of	o global warming than ins a refrigerant fluid v I to the atmosphere, th	a refrigerant with a GWP e ne impact on to interfere w	t with h equal to global	erant with lower global warming potential (GWP) would higher GWP, if leaked to the atmosphere. This o 675. This means that if 1kg of this refrigerant fluid warming would be 675 times higher than 1kg of CO2, refrigerant circuit yourself or disassemble the product
Cooling mode				
SEER		8.3		
Energy efficie		A++		
Design load (			kW	
Energy consu				per year.based on standard test results.
Actual ener	gy consumption will	aepena on	now	the appliance is used and where it is located.
Heating mode (/	Average)			
SCOP		4.7		
Energy efficie	ency class	A++		
Design load (		4.5	kW	(-10°C)
Declared cap	acity	4.50	kW	(-10°C)
Back up heat	ing capacity		kW	(-10°C)
Energy consi				per year based on standard test results.
Actual ener	gy consumption will	depend on	how	the appliance is used and where it is located.
Heating mode ()	Narmer) Optional			
SCOP		5.9		
Energy efficie	ancy class	A+++		
Design load (			kW	(2°C)
Declared cap		6.00		(2°C)
Back up heat			kW	(2°C)
Energy consi				per year.based on standard test results.
				the appliance is used and where it is located.
	0,		-	
Heating mode (	Colder) Optional			
SCOP		-		
Energy efficie		-		
Design load (			kW	(-22°C)
Declared cap	3		kW	(-22°C)
Back up heat			kW	(-22°C)
Energy consi				per year based on standard test results.
Actual ener	gy consumption will	depend on	how	the appliance is used and where it is located.
Sound nowe	level (indoor)	E0		dB(A)
	level (indoor)	59 63		dB(A)
		00		