

Indoor unit model name SRK35ZS-WT Outdoor unit model name SRC35ZS-W

Defilment	D 00			75	
Refrigerant	R32	GWP	ť	75	
contribute less to appliance contai would be leaked over a period of	o global warming than ns a refrigerant fluid w to the atmosphere, th	a refrigerant with a GWP e ie impact on o interfere w	t with h equal to global	erant with lower global warming po gher GWP, if leaked to the atmos 675. This means that if 1kg of this warming would be 675 times high efrigerant circuit yourself or disas	phere. This s refrigerant fluid er than 1kg of CO2,
Cooling mode					
SEER		8.4			
Energy efficie		A++			
Design load (kW		
Energy consu				per year.based on standard	
Actual ener	gy consumption will	depend on	how t	ne appliance is used and wher	e it is located.
Hooting mode ((vorage)				
Heating mode (A	velaye)	4.7			
Energy efficie	nev class	4.7 A++			
Design load (kW	(-10°C)	
Declared cap		3.00		(-10°C)	
Back up heat	5		kW	(-10°C)	
Energy consu				per year.based on standard	test results.
				ne appliance is used and when	
	Varmer) Optional				
SCOP		6.0			
Energy efficie		A+++			
Design load (kW	(2°C)	
Declared cap		3.70		(2°C)	
Back up heat			kW	(2°C)	
Energy consu				per year based on standard	
Actual ener	gy consumption will	depend on	how t	ne appliance is used and when	e it is located.
Heating mode (0	Coldor) Ontional				
SCOP					
Energy efficie	ancy class	-			
Design load (-	kW	(-22°C)	
Declared cap			kW	(-22°C)	
Back up heat			kW	(-22°C)	
Energy const				per year.based on standard	test results
	· ·			he appliance is used and wher	
	a, consumption will				
Sound power	level (indoor)	54		dB(A)	
	level (outdoor)	61		dB(A)	