

Indoor unit model name FDT100VH Outdoor unit model name FDC100VSA-W

Refrigerant	R32	GWP	6	75	
Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.					
Cooling mode SEER Energy efficie		7.2 A++			
Design load(Energy consu Actual energ	imption,		kWh		l on standard test results. used and where it is located.
Heating mode (A SCOP	verage)	4.6			
Energy efficie	ncv class	4.0 A++			
Design load (kW	(-10°C)	
Declared cap		8.50		(-10°C)	
Back up heat	5		kW	(-10°C)	
Energy consu		2590	kWh		on standard test results.
Actual ener	gy consumption will	depend on	how t	he appliance is ι	used and where it is located.
Heating mode (V SCOP	Varmer) Optional	_			
Energy efficie	ncy class				
Design load (-	kW	(2°C)	
Declared cap			kW	(2°C)	
Back up heat			kW	(2°C)	
Energy consu					on standard test results.
Actual energy consumption will depend on how the appliance is used and where it is located.					
Heating mode (C	Colder) Optional				
SCOP `	, ,	-			
Energy efficie	ncy class	-			
Design load (Pdesignh)		kW	(-22°C)	
Declared cap			kW	(-22°C)	
Back up heati			kW	(-22°C)	
Energy consumption, - kWh per year.based on standard test results.					
Actual energy consumption will depend on how the appliance is used and where it is located.					
	level (indoor)	62		dB(A)	
Sound power	level (outdoor)	69		dB(A)	