

Indoor unit model name FDTC50VH, FDTC60VH Outdoor unit model name SCM80ZS-W

Refrigerant	R32	GWP	f	675	
rteingerunt	1.02	0111	,		
-	-	-	-	jerant with lower global warming potential (GWP) w higher GWP, if leaked to the atmosphere. This	ould
				o 675. This means that if 1kg of this refrigerant fluid	
	-		-	warming would be 675 times higher than 1kg of CO	
-	• •		ith the	refrigerant circuit yourself or disassemble the produced	uct
yourself and alwa	ays ask a professional				
Cooling mode					
SEER		6.1			
Energy efficie		A++			
Design load (F			kW	nor year based on standard test results	
Energy consu Actual energ				per year.based on standard test results. the appliance is used and where it is located.	
Lleating mode (A					
Heating mode (A SCOP	velage)	4.0			
Energy efficier	ncv class	4.0 A+			
Design load (F			kW	(-10°C)	
Declared capa			kW	(-10°C)	
Back up heati			kW	(-10°C)	
Energy consu		2347	kWh	per year.based on standard test results.	
Actual energ	y consumption will	depend on	how t	the appliance is used and where it is located.	
Heating mode (W	/armer) Optional				
SCOP		5.1			
Energy efficie	ncy class	A+++			
Design load (F		8.5	kW	(2°C)	
Declared capa	acity	8.5	kW	(2°C)	
Back up heati		-	kW	(2°C)	
Energy consu				per year.based on standard test results.	
Actual energ	gy consumption will	depend on	how t	the appliance is used and where it is located.	
Heating mode (C	older) Optional				
SCOP		-			
SCOP Energy efficier	ncy class	-			
SCOP Energy efficien Design load (F	ncy class ² designh)		kW	(-22°C)	
SCOP Energy efficie Design load (F Declared capa	ncy class ² designh) acity	-	kW	(-22°C)	
SCOP Energy efficier Design load (F Declared capa Back up heati	ncy class Pdesignh) acity ng capacity	-	kW kW	(-22°C) (-22°C)	
SCOP Energy efficien Design load (F Declared capa Back up heatin Energy consu	ncy class Pdesignh) acity ng capacity mption,	-	kW kW kWh	(-22°C) (-22°C) per year.based on standard test results.	
SCOP Energy efficien Design load (F Declared capa Back up heatin Energy consu	ncy class Pdesignh) acity ng capacity mption,	-	kW kW kWh	(-22°C) (-22°C)	
SCOP Energy efficien Design load (F Declared capa Back up heatin Energy consu	ncy class Pdesignh) acity ng capacity mption, gy consumption will	-	kW kW kWh	(-22°C) (-22°C) per year.based on standard test results. the appliance is used and where it is located.	highest
SCOP Energy efficien Design load (F Declared capa Back up heatin Energy consu Actual energ	ncy class Pdesignh) acity ng capacity mption, gy consumption will	۔ ۔ depend on	kW kW kWh	(-22°C) (-22°C) per year.based on standard test results.	highest units.