

Indoor unit model name FDUM71VH Outdoor unit model name FDC71VNX-W

Defrigerent	DOO	GWP	6	75	
Refrigerant	R32	GVVF	0	75	
contribute less to appliance contain would be leaked over a period of 1	global warming than a ns a refrigerant fluid wi to the atmosphere, the	a refrigeran th a GWP e impact on interfere w	t with hi equal to global v	gher GWP, if leak 675. This means warming would be	obal warming potential (GWP) would ed to the atmosphere. This that if 1kg of this refrigerant fluid 675 times higher than 1kg of CO2, yourself or disassemble the product
Cooling mode					
SEER		6.9			
Energy efficie		A++			
Design load (F			kW		
Energy consu					I on standard test results. used and where it is located.
Actual energ	gy consumption will	uepenu on	now u	le appliance is t	ised and where it is located.
Heating mode (A	verage)				
SCOP	0	4.5			
Energy efficie	ncy class	A+			
Design load (F	Pdesignh)	6.0	kW	(-10°C)	
Declared capa	acity	6.00	kW	(-10°C)	
Back up heati	ng capacity	0	kW	(-10°C)	
Energy consu					l on standard test results.
Actual energ	gy consumption will	depend on	how th	ne appliance is ι	used and where it is located.
Heating mode (W	Jarmar) Ontional				
SCOP	vanner) Optional				
Energy efficier	nov class	-			
Design load (F		-	kW	(2°C)	
Declared capa			kW	(2°C) (2°C)	
Back up heati			kW	(2°C) (2°C)	
Energy consu					l on standard test results.
					used and where it is located.
	,, , , , , , , , , , , , , , , , , , ,				
Heating mode (C	older) Optional				
SCOP		-			
Energy efficier		-			
Design load (F			kW	(-22°C)	
Declared capa			kW	(-22°C)	
Back up heati			kW	(-22°C)	
Energy consu	• •				on standard test results.
Actual energ	gy consumption will	depend on	how th	ne appliance is ι	used and where it is located.
Sound nowor	level (indeer)	~-		$dB(\Lambda)$	
Sound power	level (indoor) level (outdoor)	65 66		dB(A) dB(A)	