

Indoor unit model name FDTC35VF Outdoor unit model name SRC35ZMX-S

Refrigerant	R410A	GWP	2	088	
contribute less to contains a refrige leaked to the atm	global warming than a erant fluid with a GWP nosphere, the impact o ars. Never try to interfe	a refrigerant equal to 208 n global wa	with hi 88. Thi rming v	gher GWP, if leaked to s means that if 1kg of th vould be 2088 times hig	warming potential (GWP) would the atmosphere. This appliance his refrigerant fluid would be gher than 1kg of CO2, over a sassemble the product yourself
Cooling mode					
SEER		6.2			
Energy efficie		A++			
Design load (I		3.6			
Energy consu					standard test results.
Actual energ	gy consumption will o	depend on	how t	ne appliance is used	and where it is located.
Heating mode (A	verage)				
SCOP		4.2			
Energy efficie		A+			
Design load (		3.6		(-10°C)	
Declared capa		3.00		(-10°C)	
-	ng capacity	0.60		(-10°C)	
Energy consu					standard test results.
Actual energ	gy consumption will o	depend on	how t	ne appliance is used	and where it is located.
Heating mode (V	Varmer) Optional				
SCOP	<i>,</i> .	-			
Energy efficie	ncy class	-			
Design load (	Pdesignh)	-	kW	(2°C)	
Declared capa	acity	-	kW	(2°C)	
Back up heati	ng capacity	-	kW	(2°C)	
Energy consu					standard test results.
Actual energ	gy consumption will o	depend on	how t	ne appliance is used	and where it is located.
Heating mode (C	older) Optional				
SCOP `		-			
Energy efficie	ncy class	-			
Design load (		-	kW	(-22°C)	
Declared capa	acity		kW	(-22°C)	
Back up heati			kW	(-22°C)	
	motion	_	kWh	per year.based on	standard test results.
Energy consu	πριοπ,	-			
					and where it is located.
Actual energ	gy consumption will o	depend on		ne appliance is used	
Actual energ	gy consumption will o				