

Indoor unit model name SRF35ZMX-S Outdoor unit model name SRC35ZMX-S

Defrigerent	D 4404			000	
Refrigerant	R410A	GWP	2	088	
contribute less to contains a refrigo leaked to the atm	o global warming than a erant fluid with a GWP nosphere, the impact o ars. Never try to interfe	a refrigeran equal to 20 n global wa	t with hi 88. Thi: Irming v	erant with lower global warming potential (GWP) would gher GWP, if leaked to the atmosphere. This applian is means that if 1kg of this refrigerant fluid would be would be 2088 times higher than 1kg of CO2, over a ant circuit yourself or disassemble the product yours	nce
Cooling mode					
SEER	_	6.8			
Energy efficie		A++			
Design load (			kW		
Energy consu				per year based on standard test results.	
Actual ener	gy consumption will o	depend on	how t	ne appliance is used and where it is located.	
Heating mode (A	verage)				
SCOP	(incluge)	4.3			
Energy efficie	ency class	A+			
Design load (			kW	(-10°C)	
Declared cap		2.67		(-10°C)	
Back up heat		0.63		(-10°C)	
Energy consu				per year.based on standard test results.	
				ne appliance is used and where it is located.	
	Varmer) Optional				
SCOP		-			
Energy efficie		-			
Design load (			kW	(2°C)	
Declared cap			kW	(2°C)	
Back up heat			kW	(2°C)	
Energy consu				per year.based on standard test results.	
Actual ener	gy consumption will o	depend on	now ti	ne appliance is used and where it is located.	
Heating mode (C	Colder) Ontional				
SCOP		-			
Energy efficie	ency class	_			
Design load (		_	kW	(-22°C)	
Declared cap			kW	(-22°C)	
Back up heat	3		kW	(-22°C)	
Energy consu				per year.based on standard test results.	
				ne appliance is used and where it is located.	
	J,				
Sound nowor	level (indoor)	50		dB(A)	
Sound power		57			
	level (outdoor)	52 63		dB(A)	