

Technische Daten

Variante	KWD 25	KWD 35	KWD 45	KWD 55	KWD 70	KWD 85	KWD 100
Kühlleistung	2.70 kW	3.30 kW	4.30 kW	5.40 kW	7.10 kW	8.10 kW	9.40 kW
Heizleistung	3.50 kW	4.30 kW	5.60 kW	6.90 kW	9.20 kW	10.50 kW	11.00 kW
Luftvolumenstrom Stufen	375/400/420/445/490 m³/h	395/420/440/490/520 m³/h	455/500/520/565/650 m³/h	550/620/665/740/885 m³/h	620/700/830/970/1030 m³/h	900/960/1040/1240/13 m³/h	970/1020/1140/1 m³/h
Schalldruckpegel je Stufe	27/29/32/34/35 dB(A)	29/31/32/33/35 dB(A)	31/33/35/37/39 dB(A)	34/36/38/40/42 dB(A)	31/34/37/40/42 dB(A)	35/39/41/43/45 dB(A)	37/40/42/44/47 dB(A)
Spannungsversorgung	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50
Elektr. Nennleistungsaufnahme	40 W	40 W	70 W	90 W	70 W	150 W	170 W
Elektr. Nennstromaufnahme	0.2 A	0.24 A	0.35 A	0.44 A	0.38 A	0.68 A	0.78 A
Betriebsdruck Medium, max.	1400 kPa	1400 kPa	1400 kPa	1400 kPa	1400 kPa	1400 kPa	1400 kPa
Mediumanschlüsse	3/4	3/4	3/4	3/4	3/4	3/4	3/4
Nennvolumenstrom Medium, Kühlen	0.53 m³/h	0.57 m³/h	0.75 m³/h	0.84 m³/h	1.22 m³/h	1.39 m³/h	1.45 m³/h
Mediuminhalt	1.3 l	1.3 l	1.3 l	1.79 l	2.84 l	3.22 l	3.22 l
Serienfarbton	weiß	weiß	weiß	weiß	weiß	weiß	weiß
Abmessungen Abdeckung, H/B/T	28/650/650 mm	28/650/650 mm	28/650/650 mm	28/650/650 mm	28/690/1220 mm	28/690/1220 mm	28/690/1220 mm
Gewicht	28 kg	28 kg	28 kg	31 kg	57 kg	59 kg	59 kg