

Technische Daten

Variante	KWK 125 KWK 125 DM	KWK 165 KWK 165 DM	KWK 205 KWK 205 DM	KWK 255 KWK 255 DM	KWK 305 KWK 305 DM	KWK 355 KWK 355 DM	KWK 455 KWK 455 DM	KWK 535 KWK 535 DM	KWK 595 KWK 595 DM	KWK 725 KWK 725 DM
Kühlleistung	1.20 kW	1.63 kW	2.09 kW	2.51 kW	3.08 kW	3.51 kW	4.54 kW	5.35 kW	5.92 kW	7.24 kW
Heizleistung	1.49 kW	2.02 kW	2.42 kW	2.87 kW	3.47 kW	4.03 kW	4.95 kW	5.77 kW	6.27 kW	7.65 kW
Luftvolumenstrom Stufen	120/200/260 m³/h	140/220/290 m³/h	190/290/370 m³/h	210/320/410 m³/h	280/390/490 m³/h	310/420/530 m³/h	400/570/730 m³/h	430/610/780 m³/h	420/630/870 m³/h	450/670/920 m³/h
Schalldruckpegel je Stufe	17/25/32 dB(A)	17/25/32 dB(A)	23/31/39 dB(A)	23/31/39 dB(A)	21/27/33 dB(A)	21/27/33 dB(A)	26/34/42 dB(A)	26/34/42 dB(A)	24/33/43 dB(A)	24/33/43 dB(A)
Spannungsversorgung	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50
Schutzart	X0	X0	X0	X0	X0	X0	X0	X0	X0	X0
Elektr. Nennleistungsaufnahme	35 W	39 W	47 W	51 W	59 W	71 W	97 W	107 W	120 W	139 W
Elektr. Nennstromaufnahme	0.15 A	0.17 A	0.2 A	0.22 A	0.26 A	0.31 A	0.42 A	0.47 A	0.52 A	0.6 A
Betriebsdruck Medium, max.	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa
Mediumanschlüsse	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
Nennvolumenstrom Medium, Kühlen	0.21 m³/h	0.28 m³/h	0.36 m³/h	0.43 m³/h	0.53 m³/h	0.6 m³/h	0.78 m³/h	0.92 m³/h	1.02 m³/h	1.24 m³/h
Nennvolumenstrom Medium, Heizen	0.26	0.35	0.42	0.49	0.6	0.69	0.87	0.99	1.08	1.31
Nenndruckverluste, intern Kühlen	10.5 kPa	13.3 kPa	15.3 kPa	17.3 kPa	18.6 kPa	19.9 kPa	20.2 kPa	22.6 kPa	22.6 kPa	23.4 kPa
Nenndruckverluste, intern Heizen	13 kPa	16.5 kPa	17.7 kPa	19.7 kPa	20.9 kPa	22.9 kPa	22.5 kPa	24.3 kPa	24 kPa	24.8 kPa
Mediuminhalt	0.7 l	0.7 l	1 l	1 l	1.4 l	1.4 l	1.7 l	1.7 l	2 l	2 l
Kondensatanschluss	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm
Gewicht	13.5 kg	14 kg	16.4 kg	17.2 kg	22.5 kg	23.5 kg	26 kg	27.5 kg	30 kg	31.5 kg