

Technische Daten

Variante	KWK 135 EC KWK 135 EC DM	KWK 175 EC KWK 175 EC DM	KWK 225 EC KWK 225 EC DM	KWK 265 EC KWK 265 EC DM	KWK 345 EC KWK 345 EC DM	KWK 395 EC KWK 395 EC DM	KWK 525 EC KWK 525 EC DM	KWK 605 EC KWK 605 EC DM	KWK 735 EC KWK 735 EC DM	KWK 875 EC KWK 875 EC DM
Kühlleistung	1.31 kW	1.75 kW	2.18 kW	2.60 kW	3.43 kW	3.89 kW	5.22 kW	6.06 kW	7.34 kW	8.78 kW
Heizleistung	1.63 kW	2.06 kW	2.58 kW	2.95 kW	3.81 kW	4.30 kW	5.69 kW	6.44 kW	7.76 kW	9.16 kW
Spannungsversorgung	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50
Schutzart	X0	X0	X0	X0	X0	X0	X0	X0	X0	X0
Elektr. Nennleistungsaufnahme	31 W	33 W	35 W	0.36 W	35 W	36 W	58 W	91 W	77 W	82 W
Elektr. Nennstromaufnahme	0.13 A	0.14 A	0.15 A	0.16 A	0.15 A	0.16 A	0.25 A	0.27 A	0.33 A	0.36 A
Betriebsdruck Medium, max.	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa	1500 kPa
Mediumanschlüsse	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
Nennvolumenstrom Medium, Kühlen	0.23 m³/h	0.3 m³/h	0.37 m³/h	0.45 m³/h	0.59 m³/h	0.67 m³/h	0.9 m³/h	1.04 m³/h	1.26 m³/h	1.51 m³/h
Nennvolumenstrom Medium, Heizen	0.28	0.35	0.44	0.51	0.65	0.74	0.98	1.11	1.33	1.57
Nenndruckverluste, intern Kühlen	14.4 kPa	17.1 kPa	19.3 kPa	19.4 kPa	26.8 kPa	27.5 kPa	25.7 kPa	27.6 kPa	27.7 kPa	27.8 kPa
Nenndruckverluste, intern Heizen	18 kPa	20.2 kPa	21.7 kPa	22.1 kPa	29.8 kPa	30.4 kPa	28 kPa	29.4 kPa	29.3 kPa	29 kPa
Mediuminhalt	0.7 l	0.7 l	1 l	1 l	1.4 l	1.4 l	1.7 l	1.7 l	2 l	2 l
Kondensatanschluss	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm
Gewicht	13.8 kg	14.3 kg	16.7 kg	17.5 kg	22.8 kg	23.8 kg	26.3 kg	27.8 kg	30.3 kg	31.8 kg