

INDOOR UNIT HYDROBOX

FEATURES

- Possibility of control via internet with Comfort Home application
- High efficiency
- Circulatory pump with self-regulation of speed
- Integrated expansion vessel and safety valve
- Possibility of equithermal regulation, regulation, according to the reference room temperature or by thermostat
- Possibility cooling in convector units
- Preparation of hot domestic water
- Possibility of adding a 3-way valve - not included in the package

MSH-60IB/3
MSH-100IB/3
MSH-100IB-3/9
MSH-160IB/3
MSH-160IB-3/9



Possible combinations	
Indoor	Outdoor
MSH-60IB/3	MSH-60EB
MSH-100IB/3	MSH-80EB
MSH-100IB/3	MSH-100EB
MSH-160IB/3	MSH-120EB
MSH-160IB/3	MSH-140EB
MSH-160IB/3	MSH-160EB
MSH-100IB-3/9	MSH-80EB
MSH-100IB-3/9	MSH-100EB
MSH-160IB-3/9	MSH-120EB-3
MSH-160IB-3/9	MSH-140EB-3
MSH-160IB-3/9	MSH-160EB-3

Model MSH-			60IB/3	100IB/3 100IB-3/9	160IB/3 160IB-3/9
Power supply		V / Ph / Hz	220-240 / 1 / 50		
Connecting pipe (refrigerant)	Gas	inch / mm	5/8" / 16,0		
	Liquid		1/4" / 6,0	3/8" / 9,5	
Connecting pipe (water)	Inlet	inch	1"		
	Outlet				
Safety valve		bar	3		
Leaving water temperature	Cooling	°C	5 - 25		
	Heating		25 - 65		
Main components	Water pump	Type	-		
		Speed	-		
		Max. power	W		
	Expansion tank	Volume	l	8	
Max. pressure		bar	3		
Pressure		bar	1		
Auxiliary electric heater	Mode	-	Automatic		
	Capacity	kW	3	3/9	
	Combination	-	3	3/3+3+3	
	Power supply	V / Ph / Hz	220-240 / 1 / 50		380-415 / 3 / 50
Heat exchanger	Type	-	Braze plate		
	Amount	-	1		
Level of acoustic pressure in 1m		dB (A)	28	30	32
Dimensions	Outline (w x d x h)	mm	420 x 790 x 270		
	Packaged (w x d x h)		525 x 1050 x 360		
Weight	Net	kg	37		39
	Gross		43		45

YUKON