



BUFFER TANKS FOR HEATING SYSTEMS WITH TWO HEAT EXCHANGERS

V 11/5 S2 400 75 F42 P6

Capacity	388 L
Net weight	140 kg
Insulation	50 mm
Heat exchanger surface S1	1.65 m ²
Heat exchanger surface S2	0.76
Heat exchanger capacity S1	10 L
Heat exchanger capacity S2	4.6 L
Heat losses ΔT 45K	91 W
Energy class	C
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	100
Rated pressure of the water tank	3 bar
Rated pressure of the heat exchanger	6 bar



Diameter	750 mm
Number of inlets	4 pieces
Number of outlets	5 pieces
Minimum height of the premise	1592 mm



Information

Buffer tanks for heating systems with two
heat exchangers

V 11/5 S2 400 75
F42 P6

- Low pressure buffer tanks (3 bars), designed to storage and distribute energy from up to 4 different heat sources
- Option for installation of up to 4 thermal sensors
- Highly efficient PU insulation

Serie information

Buffer tanks for heating systems with two
heat exchangers

V 11/5 S2 400 75
F42 P6

A wide range of buffer tanks with two heat exchangers for operation in closed heating systems with a volume range from 200 to 2000 liters with two heat exchangers.