



BUFFER TANKS FOR HEATING SYSTEMS WITH TWO HEAT EXCHANGERS

V15/7 S2 500 75 F42 P6

Capacity	472 L
Net weight	149.5 kg
Insulation	50 mm
Heat exchanger surface S1	2.25 m ²
Heat exchanger surface S2	1.04
Heat exchanger capacity S1	13.7 L
Heat exchanger capacity S2	6.4 L
Heat losses ΔT 45K	95 W
Energy class	C
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	110
Rated pressure of the water tank	3 bar
Rated pressure of the heat exchanger	6 bar



Diameter	750 mm
Number of inlets	4 pieces
Number of outlets	5 pieces
Minimum height of the premise	1826 mm



Information

Buffer tanks for heating systems with two
heat exchangers

V15/7 S2 500 75
F42 P6

- Low pressure buffer tanks (3 bars), designed to storage and distribute energy from up to 4 different heat sources
- Option for installation of up to 4 thermal sensors
- Highly efficient PU insulation

Serie information

Buffer tanks for heating systems with two
heat exchangers

V15/7 S2 500 75
F42 P6

A wide range of buffer tanks with two heat exchangers for operation in closed heating systems with a volume range from 200 to 2000 liters with two heat exchangers.